



LEIPA Mag plus gloss is an addition to the range of lightly coated papers, featuring a high brightness.

The brightness and highly calendered surface provide a top-quality printed finish.

Characteristics

- Whigh brightness is suitable for high-quality journals and advertising flyers
-)> Coated surface- providing ideal and sharp image reproduction

Key Benefits

- » Blue Angel certified: The demanding environmental certificate from Germany
- » EU-Ecolabel, FSC®-Recycling and PEFC™ certified.

Typical Applications

- >>> Flyers
-)> Catalogues
-)> Brochures
-)) Advertising materials

| Properties | Unit | Standard | Target Figures | | | | | | | | Tolerances |
|------------|-------|------------|----------------|------|------|------|------|------|------|------|------------|
| Grammage | g/m² | ISO 536 | 54* | 57 | 60 | 65 | 70 | 80 | 90 | 115* | +/- 4% |
| Brightness | % | ISO 2470 | 76 | 76 | 76 | 76 | 78 | 78 | 80 | 80 | +/- 4 |
| Opacity | % | DIN 53146 | ≥ 90 | ≥ 92 | ≥ 92 | ≥ 92 | ≥ 92 | ≥ 94 | ≥ 94 | ≥ 94 | |
| Gloss | % | ISO 8254-1 | ≥ 45 | ≥ 45 | ≥ 45 | ≥ 45 | ≥ 45 | ≥ 45 | ≥ 45 | ≥ 45 | |
| Bulk | cm³/g | | 0,86 | 0,86 | 0,86 | 0,86 | 0,86 | 0,88 | 0,88 | 0,94 | +/- 10% |

All values are measured under standard climate condition (23°C, 50% RH). Our measurement devices are included within the CEPI cycle.

The given technical values are for information purposes only. LEIPA Georg Leinfelder GmbH reserves the right to change product characteristics in accordance with research and market developments. The paper qualities marked with * are on demand. Please contact us, if you are interested.

Prepress

| L* a* b* target values | L* | a* | b* |
|------------------------|----|----|----|
| ISO 5631-3 (D50/2°) | 90 | 0 | 1 |

ICC-Profile

PSO LWC Standard (ECI)

Certifications









Are you interested? Please contact us.

www.leipa.com/de/graphicpaper sales@leipa.com +49 3332 24-3000

